



SPECIFICATIONS

Tubing Size (in.)	Nominal Wt. (lbs./ft.)				Grade	Wall Thick (in.)	ID (in.)	Threaded and Coupled					Integral Joint		Collaps e Resist (psi)	Internal Yield (psi)	Joint Yield Strength (lb.)			Fill-Up Volumn (bb/100 ft.)			
	Nom.	OD	T & C Non-Up	T & C Upset				Int. Jt.	Drift (in.)	Coupled OD			Drift Dia. (in.)	Box OD (in.)			Non-Up	Upset Reg.	Upset Spec.		Non-Up	T & C Upset	Int. Jt.
										Non-Up	Upset Reg.	Upset Spec.											
3/4	1.050	1.14	1.20		H-40	0.113	.824	.730	1.313	1.660					7,680	7,530	6,360	13,300		0.066			
3/4	1.050	1.14	1.20		J-55	0.113	0.824	0.730	1.313	1.660					10,560	10,360	8,740	18,290		0.066			
3/4	1.050	1.14	1.20		C-75	0.113	0.824	0.730	1.313	1.660					14,410	14,120	11,920	24,940		0.066			
3/4	1.050	1.14	1.20		N-80	0.113	0.824	0.730	1.313	1.660					15,370	15,070	12,710	26,610		0.066			
1	1.315	1.70	1.80	1.72	H-40	0.133	1.049	0.955	1.660	1.900		0.955	1.550	7,270	7,080	10,960	19,760	15,970		0.107			
1	1.315	1.70	1.80	1.72	J-55	0.133	1.049	0.955	1.660	1.900		0.955	1.550	10,000	9,730	15,060	27,160	21,960		0.107			
1	1.315	1.70	1.80	1.72	C-75	0.133	1.049	0.955	1.660	1.900		0.955	1.550	13,640	13,270	20,540	37,040	29,940		0.107			
1	1.315	1.70	1.80	1.72	N-80	0.133	1.049	0.955	1.660	1.900		0.955	1.550	14,550	14,160	21,910	39,510	31,940		0.107			
1-1/4	1.660			2.10	H-40	0.125	1.410					1.286	1.880	5,570	5,270			22,180		0.193			
1-1/4	1.660	2.30	2.40	2.33	H-40	0.140	1.380	1.286	2.054	2.200		1.286	1.880	6,180	5,900	15,530	26,740	22,180		0.185			
1-1/4	1.660			2.10	J-55	0.125	1.410					1.286	1.880	7,660	7,250			30,500		0.193			
1-1/4	1.660	2.30	2.40	2.33	J-55	0.140	1.380	1.286	2.054	2.200		1.286	1.880	8,500	8,120	21,360	36,770	30,500		0.185			
1-1/4	1.660	2.30	2.40	2.33	C-75	0.140	1.380	1.286	2.054	2.200		1.286	1.880	11,580	11,070	29,120	50,140	41,600		0.185			
1-1/4	1.660	2.30	2.40	2.33	N-80	0.140	1.380	1.286	2.054	2.200		1.286	1.880	12,360	11,810	31,060	53,480	44,370		0.185			
1-1/2	1.900			2.40	H-40	0.125	1.650					1.516	2.110	4,920	4,610			26,890		0.264			
1-1/2	1.900	2.70	2.90	2.76	H-40	0.145	1.610	1.516	2.200	2.500		1.516	2.110	5,640	5,340	19,090	31,980	26,890		0.252			
1-1/2	1.900			2.40	J-55	0.125	1.650					1.516	2.110	6,640	6,330			36,970		0.264			
1-1/2	1.900	2.75	2.90	2.76	J-55	0.145	1.610	1.516	2.200	2.500		1.516	2.110	7,750	7,350	26,250	43,970	36,970		0.252			
1-1/2	1.900	2.75	2.90	2.76	C-75	0.145	1.610	1.516	2.200	2.500		1.516	2.110	10,570	10,020	35,800	59,960	50,420		0.252			
1-1/2	1.900	2.75	2.90	2.76	N-80	0.145	1.610	1.516	2.200	2.500		1.516	2.110	11,280	10,680	38,180	63,960	53,780		0.252			
2-1/16	2.063			3.25	H-40	0.156	1.751					1.657	2.325	5,590	5,290			35,690		0.298			
2-1/16	2.063			3.25	J-55	0.156	1.751					1.657	2.325	7,690	7,280			49,070		0.298			
2-1/16	2.063			3.25	C-75	0.156	1.751					1.657	2.325	10,480	9,920			66,910		0.298			
2-1/16	2.063			3.25	N-80	0.156	1.751					1.657	2.325	11,180	10,590			71,370		0.298			
2-3/8	2.375	4.00			H-40	0.167	2.041	1.947	2.875					5,230	4,920	30,130				0.405			
2-3/8	2.375	4.60	4.70		H-40	0.190	1.995	1.901	2.875	3.063	2.910			5,890	5,600	35,960	52,170			0.387			
2-3/8	2.375	4.00			J-55	0.167	2.041	1.947	2.875					7,190	6,770	41,430				0.405			
2-3/8	2.375	4.60	4.70		J-55	0.190	1.995	1.901	2.875	3.063	2.910			8,100	7,700	49,450	71,730			0.387			
2-3/8	2.375	4.00			C-75	0.167	2.041	1.947	2.875					9,520	9,230	56,500				0.405			
2-3/8	2.375	4.60	4.70		C-75	0.190	1.995	1.901	2.875	3.063	2.910			11,040	10,500	67,430	97,820			0.387			
2-3/8	2.375	5.80	5.95		C-75	0.254	1.867	1.773	2.875	3.063	2.910			14,330	14,040	96,560	126,940			0.339			
2-3/8	2.375	4.00			N-80	0.167	2.041	1.947	2.875					9,980	9,840	60,260				0.405			
2-3/8	2.375	4.60	4.70		N-80	0.190	1.995	1.901	2.875	3.063	2.910			11,780	11,200	71,930	104,340			0.387			
2-3/8	2.375	5.80	5.95		N-80	0.254	1.867	1.773	2.875	3.063	2.910			15,280	14,970	102,990	135,400			0.339			
2-3/8	2.375	4.60	4.70		P-105	0.190	1.995	1.901	2.875	3.063	2.910			15,460	14,700	94,410	136,940			0.387			
2-3/8	2.375	5.80	5.95		P-105	0.254	1.867	1.773	2.875	3.063	2.910			20,060	19,650	135,180	177,710			0.339			
2-7/8	2.875	6.40	6.50		H-40	0.217	2.441	2.347	3.500	3.668	3.460			5,580	5,280	52,780	72,480			0.579			
2-7/8	2.875	6.40	6.50		J-55	0.217	2.441	2.347	3.500	3.668	3.460			7,680	7,260	72,580	99,660			0.579			
2-7/8	2.875	6.40	6.50		C-75	0.217	2.441	2.347	3.500	3.668	3.460			10,570	9,910	98,970	135,900			0.579			
2-7/8	2.875	8.60	8.70		C-75	0.308	2.259	2.165	3.500	3.668	3.460			14,350	14,060	149,360	185,290			0.496			
2-7/8	2.875	6.40	6.50		N-80	0.217	2.441	2.347	3.500	3.668	3.460			11,170	10,570	105,570	144,960			0.579			
2-7/8	2.875	8.60	8.70		N-80	0.308	2.259	2.165	3.500	3.668	3.460			15,300	15,000	159,310	198,710			0.496			
2-7/8	2.875	6.40	6.50		P-105	0.217	2.441	2.347	3.500	3.668	3.460			14,010	13,870	138,560	190,260			0.579			
2-7/8	2.875	8.60	8.70		P-105	0.308	2.259	2.165	3.500	3.668	3.460			20,090	19,690	209,100	260,810			0.496			
3-1/2	3.500	7.70			H-40	0.216	3.068	2.943	4.250					4,630	4,320	65,070				0.194			
3-1/2	3.500	9.20	9.30		H-40	0.254	2.992	2.867	4.250	4.500	4.180			5,380	5,080	79,540	103,610			0.870			
3-1/2	3.500	10.20			H-40	0.289	2.992	2.797	4.250					6,060	5,780	92,550				0.829			
3-1/2	3.500	7.70			J-55	0.216	3.068	2.946	4.250					5,970	5,940	89,470				0.914			
3-1/2	3.500	9.20	9.30		J-55	0.254	2.992	2.867	4.250	4.500	4.180			7,400	6,980	109,370	142,460			0.870			
3-1/2	3.500	10.20			J-55	0.289	2.992	2.797	4.250					8,330	7,950	127,250				0.829			
3-1/2	3.500	7.70			C-75	0.216	3.068	2.943	4.250					7,540	8,100	122,010				0.914			
3-1/2	3.500	9.20	9.30		C-75	0.254	2.992	2.867	4.250	4.500	4.180			10,040	9,520	149,140	194,260			0.870			
3-1/2	3.500	10.20			C-75	0.289	2.992	2.797	4.250					11,360	10,840	173,530				0.829			
3-1/2	3.500	12.70	12.95		C-75	0.375	2.750	2.625	4.250	4.500	4.180			14,350	14,060	230,990	276,120			0.735			
3-1/2	3.500	7.70			N-80	0.216	3.068	2.943	4.250					7,878	8,640	130,140				0.914			
3-1/2	3.500	9.20	9.30		N-80	0.254	2.992	2.867	4.250	4.500	4.180			10,530	10,160	159,090	207,220			0.870			
3-1/2	3.500	10.20			N-80	0.289	2.992	2.797	4.250					12,120	11,560	185,100				0.829			
3-1/2	3.500	12.70	12.95		N-80	0.375	2.750	2.625	4.250	4.500	4.180			15,310	15,000	246,390	294,530			0.735			
3-1/2	3.500	9.20	9.30		P-105	0.254	2.992	2.867	4.250	4.500	4.180			13,050	13,330	208,800	271,970			0.870			
3-1/2	3.500	12.70	12.95		P-105	0.375	2.750	2.625	4.250	4.500	4.180			20,090	19,690	323,390	386,570			0.735			
4	4.000	9.50			H-40	0.226	3.548	3.423	4.750					4,060	3,960	72,000				1.223			
4	4.000		11.00		H-40	0.262	3.476	3.351		5.000				4,900	4,580		123,070			1.174			
4	4.000	9.50			J-55	0.226	3.548	3.423	4.750					5,110	5,440	99,010				1.223			
4	4.000		11.00		J-55	0.262	3.476	3.351		5.000				6,590	6,300		169,220			1.174			
4	4.000	9.50			C-75	0.226	3.548	3.423	4.750					6,350	7,420	135,010				1.223			
4	4.000		11.00		C-75	0.262	3.476	3.351		5.000				8,410	8,600		230,750			1.174			
4	4.000	9.50			N-80	0.226	3.548	3.423															