



Midget Bridge Plug Wireline Set

The Midget Bridge Plug Series provides an economical means of zone isolation for fracturing or other treatments. The plugs are compact and require less drilling time when being removed. The plug can be set on different types of wireline pressure setting tools. This plug sustains moderate pressures and temperatures.

FEATURES:

- Electric wireline set
- Drillable
- Cast iron construction
- One piece slips - hardened to depth of wicker only
- Sets in any grade casing including P-110
- For temporary or permanent service
- Ratcheting lock ring holds setting force
- Small O.D.'s for speed and safety when running

SPECIFICATIONS for MIDGET 1

| CASING | | PLUG | | SETTING RANGE | | SETTING TOOL | |
|--------|--------------|--------------|------|---------------|-------|--------------|-------|
| OD | WT. (LBS/FT) | PART NO. | O.D. | MIN. | MAX. | BAKER | GO |
| 4 1/2 | 9.5 - 13.5 | 000-3710-001 | 3.71 | 3.920 | 4.560 | 10 | 3 1/2 |
| 5 | 11.5 - 21 | 000-3710-001 | 3.71 | 3.920 | 4.560 | 10 | 3 1/2 |
| 5 1/2 | 13 - 25 | 000-4240-001 | 4.24 | 4.580 | 5.047 | 20 | 3 1/2 |
| 5 3/4 | 22.5 - 25.2 | 000-4240-001 | 4.24 | 4.580 | 5.047 | 20 | 3 1/2 |
| 6 5/8 | 17 - 22 | 000-5610-001 | 5.61 | 5.989 | 6.655 | 20 | 3 1/2 |
| 7 | 17 - 35 | 000-5610-001 | 5.61 | 5.989 | 6.655 | 20 | 3 1/2 |

SPECIFICATIONS for MIDGET 2

| CASING | | PLUG | | SETTING RANGE | | SETTING TOOL | |
|--------|--------------|--------------|------|---------------|-------|--------------|-------|
| OD | WT. (LBS/FT) | PART NO. | O.D. | MIN. | MAX. | BAKER | GO |
| 4 1/2 | 9.5 - 16.6 | 000-3500-004 | 3.50 | 3.826 | 4.090 | 10 | 3 1/2 |
| 4 1/2 | 9.5 - 13.5 | 000-3710-004 | 3.71 | 3.920 | 4.560 | 10 | 3 1/2 |
| 5 | 11.5 - 21 | 000-3710-004 | 3.71 | 3.920 | 4.560 | 10 | 3 1/2 |
| 5 1/2 | 13 - 25 | 000-4240-004 | 4.24 | 4.580 | 5.047 | 20 | 3 1/2 |
| 5 3/4 | 22.5 - 25.2 | 000-4240-004 | 4.24 | 4.580 | 5.047 | 20 | 3 1/2 |
| 6 5/8 | 17 - 22 | 000-5610-004 | 5.61 | 5.989 | 6.655 | 20 | 3 1/2 |
| 7 | 17 - 35 | 000-5610-004 | 5.61 | 5.989 | 6.655 | 20 | 3 1/2 |



The information contained herein, is the property of Alpha Oil Tools, and is confidential. It may not be reproduced in any form without the written consent of Alpha Oil Tools. This information is subject to change without notice and does not represent a commitment on the part of Alpha Oil Tools and its representatives. Alpha plugs will not be guaranteed against failure from damage resulting from perforating above a plug which has not had cement dumped on it. This includes any other means of shock that will directly transfer to the plug.

Copyright © 1996, 1997 Alpha Oil Tools. All rights reserved.
Alpha Oil Tools / 3044 Wichita Court / Fort Worth, TX / 76140 USA
 Voice: 817-293-5192 World Wide Web: www.alphaoiltools.com

Email:
 Sales or RFO: sales@alphaoiltools.com
 Field Support Questions: fieldsupport@alphaoiltools.com
 Engineering Support: engineering@alphaoiltools.com

