



Model "B" Sleeve Valve Cement Retainer Tubing Set

The "B" Sleeve Valve Cement Retainer is a high quality tool for squeeze cementing. The sleeve valve is controlled from the surface by simply picking up to close and setting down to open.

This Retainer is set on the tubing string or drill pipe using a mechanical setting tool. The tubing may be tested before squeeze takes place. The valve is automatically closed when releasing retainer.

Conversion to wireline set is easy and requires minimal parts. The retainer sustains high pressure and temperature.

FEATURES:

- Tubing set
- Drillable
- Cast iron construction
- One piece slips - hardened to depth of wicker only
- Sets in any grade casing including P-110
- Form-fitting metal back-ups prevent rubber extrusion
- For temporary or permanent service
- Ratcheting lock ring holds setting force

SPECIFICATIONS

CASING		PLUG		SETTING RANGE	
OD	WT. (LBS/FT)	PART NO.	O.D.	MIN.	MAX.
4 1/2	9.5 - 16.6	005-3593-000	3.593	3.826	4.090
5	11.5 - 18	005-3937-000	3.937	4.154	4.560
5 1/2	13 - 23	005-4312-000	4.312	4.580	5.044
6	10.5 - 12	005-5375-000	5.375	5.595	6.135
6 5/8	17 - 34	005-5375-000	5.375	5.595	6.135
7	32 - 38	005-5375-000	5.375	5.595	6.135
7	17 - 35	005-5687-000	5.687	6.004	6.538
7 5/8	20 - 39	005-6312-000	6.312	6.625	7.263
8 5/8	24 - 49	005-7125-000	7.125	7.511	8.248
9 5/8	29.3 - 53.5	005-8125-000	8.125	8.435	9.063
10 3/4	54 - 81	005-9000-000	9.000	9.250	9.660
10 3/4	32.7 - 51	005-9437-000	9.437	9.660	10.192
13 3/8	77 - 102	005-1156-000	11.562	11.633	12.464
13 3/8	48 - 72	005-1200-000	12.000	12.175	12.715



THIS ILLUSTRATION DOES NOT REFLECT ALL SIZES

The information contained herein, is the property of Alpha Oil Tools, and is confidential. It may not be reproduced in any form without the written consent of Alpha Oil Tools. This information is subject to change without notice and does not represent a commitment on the part of Alpha Oil Tools and its representatives. Alpha plugs will not be guaranteed against failure from damage resulting from perforating above a plug which has not had cement dumped on it. This includes any other means of shock that will directly transfer to the plug.

Copyright © 1996, 1997 Alpha Oil Tools. All rights reserved.
 Alpha Oil Tools / 3044 Wichita Court / Fort Worth, TX / 76140 USA
 Voice: 817-293-5192 World Wide Web: www.alphaoiltools.com

Email:
 Sales or RFQ: sales@alphaoiltools.com
 Field Support Questions: fieldsupport@alphaoiltools.com
 Engineering Support: engineering@alphaoiltools.com

