

# Discover the legacy of the Big Boy™ Bridge Plug, the top-selling and highly trusted solution from Alpha Oil Tools. Renowned across North America and the Gulf of Mexico, this Made in the USA plug excels in reliability, longevity, and quality materials sourced domestically. With a wide range of casing diameters available, the Big Boy™ is tailored to support diverse plugging applications with unmatched precision and performance.

The Big Boy™ Bridge Plug is manufactured with drillable materials for rapid drill out.

### **FEATURES**

- Electric wireline set
- Drillable cast iron construction
- One piece grips
- Sets in any grade casing including P-110
- Form-fitting metal back-ups prevent rubber extrusion
- For temporary or permanent service
- Ratcheting lock ring holds setting force

# **BIG BOY**

### **Bridge Plug**

Wireline or Hydraulic Set





## **BIG BOY**







Part Number	Plus O.D. (in)	Tubing/Cooing O.D. (in)	Tubing/Cooing Woight (lho/ft)	Catting Dange Min (In)	Satting Dange May (In)	Satting Tool	Max Pressure	May Tomporoturo	Wireline Adenter Vit	Setting sleeve
	Plug O.D. (in)		Tubing/Casing Weight (lbs/ft)			Setting Tool		Max Temperature	Wireline Adapter Kit	
000-1710-000	1.71	2 3/8	4.0- 5.9	1.867	2.041	GO 1 11/16	10,000 psi	250F	000-1710-101	000-1710-101
000-1710-002	1.71	2 3/8	4.0- 5.9	1.867	2.041	BAKER 05	10,000 psi	250F	000-1710-200	000-1710-200
000-2100-000	2.1	2 7/8	6.4 - 6.5	2.373	2.494	GO 1 11/16	10,000 psi	250F	000-2100-101	000-2100-101
000-2100-000	2.1	2 7/8	6.4 - 6.5	2.373	2.494	GO 2 1/8	10,000 psi	250F	000-2100-102	000-2100-102
000-2100-002	2.1	2 7/8	6.4 - 6.5	2.373	2.494	BAKER 05	10,000 psi	250F	000-2100-200	000-2100-200
000-2500-000	2.5	3 1/2	9.2 - 12.95	2.75	2.992	GO 1 11/16	10,000 psi	250F	000-2500-101	000-2500-101
000-2500-000	2.5	3 1/2	9.2 - 12.95	2.75	2.992	GO 2 1/8	10,000 psi	250F	000-2500-102	000-2500-102
000-2500-002	2.5	3 1/2	9.2 - 12.95	2.75	2.992	BAKER 05	10,000 psi	250F	000-2500-200	000-2500-200
000-2750-000	2.75	3 1/2	5.7 - 10.2	2.922	3.068	BAKER 10	10,000 psi	250F	000-2750-900	000-2750-210
000-2750-000	2.75	3 1/2	5.7 - 10.2	2.922	3.068	GO 1 11/16	10,000 psi	250F	000-2750-101	000-2750-101
000-2750-000	2.75	3 1/2	5.7 - 10.2	2.922	3.068	GO 2 1/8	10,000 psi	250F	000-2750-102	000-2750-102
000-2750-002	2.75	3 1/2	5.7 - 10.2	2.922	3.068	BAKER 05	10,000 psi	250F	000-2750-200	000-2750-200
000-3120-002	3.12	4	9.5 - 13.2	3.34	3.548	BAKER 10	10,000 psi	250F	000-3120-900	000-3120-200
000-3120-002	3.12	4	9.5 - 13.2	3.34	3.548	GO 2 1/8	10,000 psi	250F	000-3120-100	000-3120-100
000-3500-002	3.5	4 1/2	9.5 - 15.1	3.826	4.09	BAKER 10	10,000 psi	250F	000-3500-900	000-3500-200
000-3500-002	3.5	4 1/2	9.5 - 15.1	3.826	4.09	GO 3 1/2	10,000 psi	250F	000-3500-930	000-3500-100
000-3710-002	3.71	4 1/2	9.5 - 13.5	3.92	4.56	BAKER 10	10,000 psi	250F	000-3500-900	000-3500-200
000-3710-002	3.71	4 1/2	9.5 - 13.5	3.92	4.56	GO 3 1/2	10,000 psi	250F	000-3500-930	000-3500-100
000-3710-002	3.71	5	11.5-24.1	3.92	4.56	BAKER 10	10,000 psi	250F	000-3500-900	000-3500-200
000-3710-002	3.71	5		3.92	4.56	GO 3 1/2		250F	000-3500-930	
			11.5—24.1				10,000 psi			000-3500-100
000-4240-002	4.24	5 1/2	15.5 - 26	4.548	5.012	BAKER 10	10,000 psi	250F	000-4240-910	000-4240-210
000-4240-002	4.24	5 1/2	15.5 - 26	4.548	5.012	GO 3 1/2	10,000 psi	250F	000-4240-930	000-4240-100
000-4240-002	4.24	5 3/4	21.8-24.2	4.548	5.012	BAKER 20	10,000 psi	250F	000-4240-900	000-4240-200
000-4240-002	4.24	5 3/4	21.8-24.2	4.548	5.012	GO 3 1/2	10,000 psi	250F	000-4240-930	000-4240-100
000-4750-002	4.75	6	18 - 26	5.132	5.595	BAKER 20	10,000 psi	250F	000-4240-900	000-4240-200
000-4750-002	4.75	6	18 - 26	5.132	5.595	GO 3 1/2	10,000 psi	250F	000-4240-930	000-4240-100
000-4750-002	4.75	6 5/8	34	5.132	5.595	BAKER 20	10,000 psi	250F	000-4240-900	000-4240-200
000-4750-002	4.75	6 5/8	34	5.132	5.595	GO 3 1/2	10,000 psi	250F	000-4240-930	000-4240-100
000-5340-002	5.34	6 5/8	20 - 32	5.626	6.094	GO 3 1/2	10,000 psi	250F	000-5610-930	000-5610-100
000-5340-002	5.34	6 5/8	20 - 32	5.626	6.094	BAKER 20	10,000 psi	250F	000-5610-900	000-5610-200
000-5340-002	5.34	7	32-46.4	5.626	6.094	GO 3 1/2	10,000 psi	250F	000-5610-930	000-5610-100
000-5340-002	5.34	7	32-46.4	5.626	6.094	BAKER 20	10,000 psi	250F	000-5610-900	000-5610-200
000-5610-002	5.61	6 5/8	20-24	5.921	6.538	GO 3 1/2	10,000 psi	250F	000-5610-930	000-5610-100
000-5610-002	5.61	6 5/8	20-24	5.921	6.538	BAKER 20	10,000 psi	250F	000-5610-900	000-5610-200
000-5610-002	5.61	7	20 – 35	5.921	6.538	GO 3 1/2	10,000 psi	250F	000-5610-930	000-5610-100
000-5610-002	5.61	7	20 – 35	5.921	6.538	BAKER 20	10,000 psi	250F	000-5610-900	000-5610-200
000-6090-002	6.09	7 5/8	24 - 39	6.625	7.025	GO 3 1/2	10,000 psi	250F	000-6090-930	000-6090-100
000-6090-002	6.09	7 5/8	24 - 39	6.625	7.025	BAKER 20	10,000 psi	250F	000-6090-900	000-6090-200
000-6960-002	6.96	8 5/8	24 - 49	7.511	8.097	BAKER 20	8,000 psi	250F	000-6960-900	000-6960-200
000-6960-002	6.96	8 5/8	24 - 49	7.511	8.097	GO 3 1/2	8,000 psi	250F	000-6960-930	000-6960-100
000-7710-002	7.71	9 5/8	32.3 - 64.9	8.281	9.001	BAKER 20	8,000 psi	250F	000-7710-900	000-7710-200
000-7710-002	7.71	9 5/8	32.3 - 64.9	8.281	9.001	GO 3 1/2	8,000 psi	250F	000-7710-930	000-7710-100
000-8710-002	8.71	10 3/4	55.5 - 79.2	9.282	9.76	BAKER 20	5,000 psi	250F	000-8710-900	000-8710-200
000-8710-002	8.71	10 3/4	55.5 - 79.2	9.282	9.76	GO 3 1/2	5,000 psi	250F	000-8710-930	000-8710-100
000-9500-002	9.5	10 3/4	32.75 - 51	9.85	11.084	BAKER 20	5,000 psi	250F	000-9500-900	000-9500-200
000-9500-002	9.5 9.5	10 3/4	32.75 - 51 42 - 71	9.85 9.85	11.084 11.084	GO 3 1/2 BAKER 20	5,000 psi 5,000 psi	250F 250F	000-9500-930	000-9500-100
000-9500-002	9.5	11 3/4	42 - 71	9.85	11.084	GO 3 1/2	5,000 psi	250F 250F	000-9500-900	000-9500-200
000-9500-002										
	11.56	13 3/8	77 - 100.3	11.751	12.546	BAKER 20	3,000 psi	250F	000-1156-900	000-1156-200
000-1156-002	11.56	13 3/8	77 - 100.3	11.751	12.546	BAKER 20	3,000 psi	250F	000-1156-930	000-1156-100
000-1200-002	12	13 3/8	48 - 72	12.191	12.931	BAKER 20	3,000 psi	250F	000-1200-900	000-1200-200
000-1200-002	12	13 3/8	48 - 72	12.191	12.931	GO 3 1/2	3,000 psi	250F	000-1200-930	000-1200-100
000-1200-002	12	13 1/2	81.4	12.191	12.931	BAKER 20	3,000 psi	250F	000-1200-900	000-1200-200
000-1200-002	12	13 1/2	81.4	12.191	12.931	GO 3 1/2	3,000 psi	250F	000-1200-930	000-1200-100
000-1200-002	12	13 5/8	88.2	12.191	12.931	BAKER 20	3,000 psi	250F	000-1200-900	000-1200-200
000-1200-002	12	13 5/8	88.2	12.191	12.931	GO 3 1/2	3,000 psi	250F	000-1200-930	000-1200-100
000-1200-002	12	14	82.5—116	12.191	12.931	BAKER 20	3,000 psi	250F	000-1200-900	000-1200-200
000-1200-002	12	14	82.5—116	12.191	12.931	GO 3 1/2	3,000 psi	250F	000-1200-930	000-1200-100
000-1425-002	14.25	16	65 - 109	14.5	15.504	GO 3/12	2,000 psi	250F	000-1425-930	000-1425-100
000-1425-002	14.25	16	65 - 109	14.5	15.504	BAKER 20	2,000 psi	250F	000-1425-900	000-1425-200
000-1725-002	14.25	18 5/8	76-96.5	17.655	18.73	GO 3/12	2,000 psi	250F	000-1425-930	000-1425-100
000-1725-002	14.25	18 5/8	76—96.5	17.655	18.73	BAKER 20	2,000 psi	250F	000-1425-900	000-1425-200
000-1725-002	17.25	20	133 - 169	17.655	18.73	BAKER 20	2,000 psi	250F	000-1725-900	000-1725-200
000-1725-002	17.25	20	133 - 169	17.655	18.73	GO 3 1/2	2,000 psi	250F	000-1725-930	000-1725-100