



# B-1

## Bridge Plug


Wireline

The B-1 Bridge Plug: a top-tier solution offering cost-effective temporary zone isolation for treatments. Designed for versatility, this plug can be set on wireline pressure setting tools and easily converted to a mechanical set with minimal parts change. With robust construction, the B-1 Bridge Plug maintains integrity under high pressures and temperatures, ensuring reliable performance in demanding environments.

The B-1 bridge plug is manufactured with drillable material for rapid drill out.

## FEATURES

- Electric wireline set
- Drillable cast iron construction
- Sets in any grade casing including P-110
- Form-fitting metal back-ups prevent rubber extrusion
- For temporary or permanent service
- Ratcheting lock ring holds setting force
- Can be upgraded to 400F temperature rating upon request



# B-1

## Bridge Plug

### Wireline



Part Number	Plug O.D. (in)	Tubing/Casing O.D. (in)	Tubing/Casing Weight (lbs/ft)	Setting Range Min. (in)	Setting Range Max. (in)	Setting Tool	Max Pressure psi	Max Temperature F	Wireline Adapter Kit	Setting sleeve	GO Adapter
005-3593-003	3.593	4 1/2	9.5 - 15.1	3.826	4.090	BAKER 20	10,000	250	005-3593-900	005-3593-200	000-3500-260
005-3937-003	3.937	5	11.5—20.3	4.184	4.560	BAKER 20	10,000	250	005-3937-900	005-3937-200	000-3500-270
005-3937-003	3.937	5 1/2	29.7 —32.6	4.184	4.560	BAKER 20	10,000	250	005-3937-900	005-3937-200	000-3500-270
005-4312-003	4.312	5 1/2	15.5 - 26	4.67	5.012	BAKER 20	10,000	250	005-3937-900	005-3937-200	000-3500-270
005-4312-003	4.312	5 3/4	21.8—24.2	4.67	5.012	BAKER 20	10,000	250	005-3937-900	005-3937-200	000-3500-270
005-4750-003	4.75	6	18 - 26	5.132	5.424	BAKER 20	10,000	250	005-4750-900	005-4750-200	000-3500-270
005-5375-003	5.375	6 5/8	20 - 32	5.625	6.094	BAKER 20	10,000	250	005-5687-900	005-5687-200	000-3500-270
005-5375-003	5.375	7	32-46.4	5.625	6.094	BAKER 20	10,000	250	005-5687-900	005-5687-200	000-3500-270
005-5687-003	5.687	7	20— 35	5.876	6.625	BAKER 20	10,000	250	005-5687-900	005-5687-200	000-3500-270
005-5687-003	5.687	7 5/8	47.1 — 59.2	5.876	6.625	BAKER 20	10,000	250	005-5687-900	005-5687-200	000-3500-270
005-5687-003	5.687	7 3/4	51.8 — 56.1	5.876	6.625	BAKER 20	10,000	250	005-5687-900	005-5687-200	000-3500-270
005-6312-003	6.312	7 5/8	24 - 39	6.625	7.025	BAKER 20	10,000	250	005-6312-900	005-6312-200	000-3500-270
005-7125-003	7.125	8 5/8	24 - 49	7.511	8.097	BAKER 20	8,000	250	005-7125-900	005-7125-200	000-3500-270
005-8125-003	8.125	9 5/8	32.3 - 53.50	8.535	9.001	BAKER 20	8,000	250	005-8125-900	005-8125-200	000-3500-270
005-9000-003	9.000	10 3/4	60.7 - 79.2	9.282	9.660	BAKER 20	5,000	250	005-9000-900	005-9000-200	000-3500-270
005-9437-003	9.437	10 3/4	32.75 - 60.7	9.660	10.192	BAKER 20	5,000	250	005-9437-900	005-9437-200	000-3500-270
005-9500-003	9.500	10 3/4	32.75 - 51	9.850	11.084	BAKER 20	5,000	250	005-9437-900	005-9437-200	000-3500-270
005-9937-003	9.937	11 3/4	60 —83	10.190	10.772	BAKER 20	4000	250	005-9937-900	005-9937-200	000-3500-270
005-9937-003	9.937	11 7/8	71.8	10.190	10.772	BAKER 20	4000	250	005-9937-900	005-9937-200	000-3500-270
005-1200-003	12.00	13 3/8	48 - 72	12.347	12.715	BAKER 20	3,000	250	005-1200-900	005-1200-200	000-3500-270
005-1200-003	12.00	13 1/2	81.4	12.347	12.715	BAKER 20	3,000	250	005-1200-900	005-1200-200	000-3500-270
005-1200-003	12.00	13 5/8	88.2	12.347	12.715	BAKER 20	3,000	250	005-1200-900	005-1200-200	000-3500-270
005-1425-003	14.25	16	65 - 109	14.688	15.250	BAKER 20	2000	250	005-1425-900	005-1425-200	000-3500-270
005-1725-003	17.25	18 5/8	76—96.5	17.655	18.730	BAKER 20	2,000	250	005-1725-900	005-1725-200	000-3500-270
005-1725-003	17.25	20	133 - 169	17.655	18.730	BAKER 20	2,000	250	005-1725-900	005-1725-200	000-3500-270



alphaoiltools.com