

EXTRA RANGE BRIDGE PLUG

Let us introduce the **Extra Range Bridge Plug**: a specialized plug designed to navigate through restrictions and still securely set in larger diameters. Common obstructions like seating nipples often necessitate tubing removal before well service can proceed. However, the Extra Range Bridge Plug mitigates this need in many cases, streamlining operations and saving valuable time.

FEATURES

- Wireline set. (GO)
- Not Pressure rated.
- Millable.
- Sets in any grade tubing including P-110.
- Form fitting metal back-ups prevent rubber extrusion.
- Permanent service.
- Ratcheting lock ring holds setting force
- Runs through restrictions to set in larger diameters.
- Can be upgraded to 400F temperature rating upon request.
- Available sizes for setting range from 1.610 to 3.920 in.



ALPHA EXTRA RANGE BRIDGE PLUG SIZE CHART

| Part Number | OD (in) | Setting Range Min (in) | Setting Range Max (in) | Setting Tool |
|--------------|---------|------------------------|------------------------|-----------------|
| 001-1406-000 | 1.406 | 1.610 | 1.995 | GO 1.500 |
| 001-1750-000 | 1.750 | 1.905 | 2.441 | GO 1.687 |
| 001-1906-000 | 1.906 | 2.156 | 2.765 | GO 1.687 |
| 001-2187-000 | 2.187 | 2.375 | 3.000 | GO 1.687/ 2.125 |
| 001-2281-000 | 2.281 | 2.441 | 3.343 | GO 1.687/ 2.125 |
| 001-2500-000 | 2.500 | 2.625 | 3.500 | GO 2.125 |
| 001-2750-000 | 2.750 | 3.187 | 3.920 | GO 2.125 |



Made In The USA