

H-M BRIDGE PLUG

Introducing the Alpha **H-M Bridge Plug**: engineered to withstand high pressure and temperature conditions with ease. This plug revolutionizes the setting process, utilizing hydraulic power to engage the top slips and then employing mechanical pull to finalize the set. Unlike traditional methods, there's no need for a separate mechanical setting tool as the mechanism is integrated within the plug itself.

FEATURES

- Drillable cast iron construction
- Sets in any grade casing including P-110
- Metal back-up to prevent rubber extrusion
- For permanent service
- Ratcheting lock ring holds setting force
- Excellent for deviated wells
- Can be upgraded to 400°F temperature rating upon request

Part Number H-M BP	Plug OD (in)	Setting Range Min (in)	Setting Range Max (in)	Max Pressure (psi)
000-2750-055	2.750	2.922	3.068	10,000
000-3120-055	3.120	3.340	3.548	10,000
000-3500-055	3.500	3.826	4.090	10,000
000-3500-065				6,000
000-3710-055	3.710	3.920	4.408	10,000
000-4240-055	4.240	4.548	5.012	10,000
000-4240-065				6,000
000-4750-055	4.750	5.007	5.595	10,000
000-5340-055	5.340	5.626	6.094	10,000
000-5610-055	5.610	5.921	6.538	10,000
000-5610-065				6,000
000-6090-055	6.090	6.625	7.025	10,000
000-6960-055	6.960	7.511	8.097	8,000
000-7710-055	7.710	8.281	9.001	8,000
000-8690-055	8.690	9.000	9.342	5,000
000-8710-055	8.710	9.282	9.760	5,000
000-9500-055	9.500	9.850	10.369	5,000
000-1200-055	12.00	12.347	12.715	3,000
000-1425-055	14.25	14.688	15.250	2,000
000-1725-055	17.25	17.655	18.730	2,000
000-1800-055	18.00	18.730	20.312	2,000



ALPHA
OIL TOOLS

Made In The USA